

Power Output Ratings

50 Hz / 400 V

Standby Power (ESP)	kVA	155
	kW	124
Prime Power (PRP)	kVA	140
	kW	112

Standby Power (ESP)

Manufacturer		PERKINS
Model		1006TAG
No of Cylinder / Configuration		6 - INLINE
Displacement	lt	5,99
Bore / Stroke	mm	100 / 127
Compression Ratio		17:01
Aspiration		Turbocharged and Air-to-Air Charged Cooled
Governor Type		ELECTRONIC
Cooling System		WATER
Coolant Capacity	lt	37,22
Lubrication Oil Capacity	lt	19
Electrical System	VDC	12
Speed / Frequency		1500 rpm / 50 Hz
Engine Gross Power	kWm	141
Fuel Consumption	110 %	34,6
	100 %	31,5
	75 %	24,1
	50 %	16,5
Exhaust Outlet Temperature	°C	585
Exhaust Gas Flow	m³/min	25,71
Combustion Air Flow	m³/min	8,78
Cooling Air Flow	m³/min	154

Alternator

Manufacturer		MARELLI
Model		MJB250MA4
No of Phase		3
Power Factor		0,8
No of Bearing		SINGLE
No of Poles		4
No of Leads		12
Voltage Regulation (Steady State)		± %0,5
Insulation Class		H
Degree of Protection		IP 23
Excitation System		AVR (Automatic Voltage Regulator), Brushless
Connection Type		STAR
Total Harmonic Content (No Load)		< %2
Frequency	Hz	50
Voltage Output	VAC	230 / 400
Rated Power (Standby)	kVA	180
Efficiency	%	92,9

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise dB(A) @ 1m
Canopied	1100 x 3320 x 1600	1864	260	78
Open Skid	1100 x 2350 x 1350	1464	260	TBA





Standby Power

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
- Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
- All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask

TBD: To Be Determined

NA: Not Available

N/A: Not Applicable

TTD155PE5A0414-EN

www.teksangenerator.com

