


Power Output Ratings		50 Hz / 400 V
Standby Power (ESP)	kVA	450
	kW	360
Prime Power (PRP)	kVA	409
	kW	327

Standby Power (ESP)		
Manufacturer		PERKINS
Model		2206A-E13TAG3
No of Cylinder / Configuration		6 - INLINE
Displacement	lt	12,5
Bore / Stroke	mm	130 / 157
Compression Ratio		16,3:1
Aspiration		Turbocharged and Air-to-Air Charged Cooled
Governor Type		ELECTRONIC/ECM
Cooling System		WATER
Coolant Capacity	lt	51,4
Lubrication Oil Capacity	lt	40
Electrical System	VDC	24
Speed / Frequency		1500 rpm / 50 Hz
Engine Gross Power	kWm	412,5
Fuel Consumption	110 %	90
	100 %	89
	75 %	81
	50 %	62
Exhaust Outlet Temperature	°C	630
Exhaust Gas Flow	m³/min	72,5
Combustion Air Flow	m³/min	26,4
Cooling Air Flow	m³/min	654

Alternator		
Manufacturer		MARELLI
Model		MJB315MA4
No of Phase		3
Power Factor		0,8
No of Bearing		SINGLE
No of Poles		4
No of Leads		12
Voltage Regulation ( Steady State)		± %0,5
Insulation Class		H
Degree of Protection		IP 23
Excitation System		AVR (Automatic Voltage Regulator), Brushless
Connection Type		STAR
Total Harmonic Content (No Load)		< %2
Frequency	Hz	50
Voltage Output	VAC	230 / 400
Rated Power (Standby)	kVA	450
Efficiency	%	93,7

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise dB(A) @ 1m
Canopied	1650 x 5000 x 2250	3488	900	TBA
Open Skid	1650 x 3300 x 2050	2788	900	TBA





### Standby Power

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

### Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
- Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
- All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask

TBD: To Be Determined

NA: Not Available

N/A: Not Applicable

TTD450PE5A0414-EN

[www.teksangenerator.com](http://www.teksangenerator.com)

