

Power Output Ratings		50 Hz / 400 V
Standby Power (ESP)	kVA	67
	kW	54
Prime Power (PRP)	kVA	61
	kW	49

Standby Power (ESP)		
Manufacturer		PERKINS
Model		1103A-33TG2
No of Cylinder / Configuration		3 - INLINE
Displacement	lt	3,3
Bore / Stroke	mm	105 / 127
Compression Ratio		17,25:1
Aspiration		Turbocharged
Governor Type		MECHANIC
Cooling System		WATER
Coolant Capacity	lt	10,2
Lubrication Oil Capacity	lt	8,3
Electrical System	VDC	12
Speed / Frequency		1500 rpm / 50 Hz
Engine Gross Power	kWm	60,5
Fuel Consumption	110 %	15,6
	100 %	14,1
	75 %	10,5
	50 %	7,3
Exhaust Outlet Temperature	°C	543
Exhaust Gas Flow	m³/min	9,8
Combustion Air Flow	m³/min	3,8
Cooling Air Flow	m³/min	110,4

Alternator		
Manufacturer		MARELLI
Model		MJB200MA4
No of Phase		3
Power Factor		0,8
No of Bearing		SINGLE
No of Poles		4
No of Leads		12
Voltage Regulation (Steady State)		± %1
Insulation Class		H
Degree of Protection		IP 23
Excitation System		AVR (Automatic Voltage Regulator), Brushless
Connection Type		STAR
Total Harmonic Content (No Load)		< %2
Frequency	Hz	50
Voltage Output	VAC	230 / 400
Rated Power (Standby)	kVA	68
Efficiency	%	90,1

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise dB(A) @ 1m
Canopied	950 x 2650 x 1450	1129	160	73
Open Skid	950 x 2000 x 1230	834	160	TBA





Standby Power

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask

TBD: To Be Determined

NA: Not Available

N/A: Not Applicable

TTD67PE5A0414-EN

www.teksangenerator.com

